

DH-HAC-HDW1209TLQ-LED

2MP Full-color Starlight HDCVI Eyeball Camera



- Full-color starlight
- 20 m illumination distance
- Max. 30fps@1080P
- CVI/CVBS/AHD/TVI switchable
- Fixed lens (2.8 mm;3.6 mm optional)
- IP67, 12V±30% DC



System Overview

Experience 2MP full HD color video and the simplicity of reusing existing coaxial infrastructure with HDCVI. The full-color starlight HDCVI camera presents a high quality color image with rich details even in total dark conditions. It offers various fixed lens models with a multi-language OSD and HD/SD switchable output. It adopts one powerful warm white LED illuminators, covering an effective range up to 20 m (65.61 ft). The LEDs switch on automatically in darkness to capture detail-packed full-color images 24/7, ensuring authentic identification of objects. It is an ideal choice for applications such as schools, retail centers and parking lots.

Functions

Full-color Starlight

The camera adopts F1.6 large aperture lens and 1/2.8" high performance sensor. With higher amount of absorbed light and advanced image processing algorithm, the camera presents an impressive lowlight performance with an exceptional balance between noise reduction and the blur of moving object.

Warm Supplemental lights

With one warm supplemental LED lights, the camera is able to provide a colorful and vivid image even in total dark. By default, the camera is set to smart light mode, in which the camera can automatically adjust the exposure time and light sensitivity simultaneously to avoid overexposure of the objects in the image center. Also, the sensitivity and intensity of the LED lights can be remotely controlled by OSD menu.

Broadcast-quality Audio*

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

*This function is available for select models.

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm.

*Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees long-distance and real-time transmission without any loss. It supports up to 700 m for 2MP HD video via coaxial cable, and up to 300 m via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Multiple-formats




The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820 (UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Lite Series | DH-HAC-HDW1209TLQ-LED

Technical Specification						Noise Reduction		2D NR	
Camera						Smart Light		Yes	
Image Sensor		1/2.8 inch CMOS				Mirror		Off/On	
Effective Pixels		1920 (H) × 1080 (V), 2MP				Privacy Masking		Off/On (8 area, rectangle)	
Scanning System		Progressive				Certifications			
Electronic Shutter Speed		PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s				Certifications		CE (EN55032, EN55024, EN50130-4,EN60950-1) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)	
S/N Ratio		>65dB				Port			
Minimum Illumination		0.01Lux/F1.6, 0Lux white light on				Video Output		Video output choices of CVI/TVI/AHD/CVBS by one BNC port	
Illumination Distance		Distance up to 20 m (65.61 ft)				Power			
Illuminator On/Off Control		Auto; manual				Power Supply		12V ±30% DC	
Illuminator Number		1				Power Consumption		Max 3.0W (12V DC, White Light on)	
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°-78 Rotation: 0°–360°				Environment			
Lens						Operating Temperature		-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)	
Lens Type		Fixed-focal				Storage Temperature		-40°C to +60°C (-40°F to 140°F); <95% (non-condensation)	
Mount Type		M12				Protection Grade		IP67	
Focal Length		2.8 mm ;3.6 mm				Structure			
Max. Aperture		F1.6 ;F1.6				Casing		Inner core: metal + plastic Cover: plastic Pedestal: plastic	
Field of View		2.8 mm: 126.2° × 106° × 56.5° (diagonal × horizontal × vertical); 3.6 mm: 103.6° × 86.9° × 46.3° (diagonal × horizontal × vertical)				Camera Dimensions		φ97.1 mm × 91.4 mm (φ3.82" × 3.6")	
Iris Type		Fixed iris				Net Weight		0.21 Kg (0.46 lb)	
Close Focus Distance		2.8 mm: 0.6 m (1.97 ft); 3.6 mm: 1.2 m (3.94 ft)				Gross Weight		0.28 Kg (0.62 lb)	
DORI Distance	Lens	Detect	Observe	Recognize	Identify				
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (26.3 ft)	3.9 m (12.8 ft)				
	3.6 mm	55.2 m (181.1 ft)	22.1 m (72.5 ft)	11.0 m (36.1 ft)	5.5 m (18.0 ft)				
Video									
Frame Rate		CVI: PAL: 1080P@25fps; 720P@25fps; NTSC: 1080P@30fps; 720P@30fps; AHD: PAL: 1080P@25fps; NTSC: 1080P@30fps TVI: PAL: 1080P@25fps; NTSC: 1080P@30fps CVBS: PAL: 960H; NTSC: 960H							
Resolution		1080P (1920 × 1080); 720P (1280× 720); 960H (960 × 576/960 × 480)							
BLC		BLC/WDR							
WDR		DWDR							
White Balance		Auto; manual							
Gain Control		Auto; manual							

Ordering Information			Junction Mount	Junction Mount
Type	Part Number	Description	PFA13G	PFA130-E
2MP Camera	DH-HAC-HDW1209TLQP-LED 2.8 mm	2MP Full-color Starlight HDCVI Eyeball Camera		
	DH-HAC-HDW1209TLQN-LED 2.8 mm			
	DH-HAC-HDW1209TLQP-LED 3.6 mm			
	DH-HAC-HDW1209TLQN-LED 3.6 mm			
Accessories	PFA13G	Junction Box	Wall Mount	Pole Mount (Vertical)
	PFA130-E	IP66 Junction Box	PFB205W	PFA152-E+PFB205W
	PFB205W	Wall Mount Bracket		
	PFA152-E	Pole Mount Bracket		
	PFM321D	12V 1A Power Adapter		
	PFM904	Integrated Mount Tester		
	PFM820	UTC controller (Only 1080P and below are available)		
	PFM800-E	Passive HDCVI Balun		

Accessories

Dimensions (mm[inch])

Optional:



PFA13G
Junction Box



PFA130-E
IP66 Junction Box



PFB205W
Wall Mount Bracket



PFA152-E
Pole Mount Bracket



PFM321D
12V 1A Power Adapter



PFM904
Integrated Mount Tester



PFM820
UTC controller
(Only 1080P and below
are available)



PFM800-E
Passive HDCVI Balun

